



### DESCRIPTION


High reliability and precision alignment. Easy to use. Can be widely used for FTT, passive optical network (OPN) and cable TV network (CATV). Low Insertion loss and return loss. Good repeatability, changeability and temperature stabilization. Include dust protections caps. Allow fitting in the bulkheads patch panel either with a nut or with clips.



B2000/APC SIMPLEX



B2000/APC - SC/APC SIMPLEX



B2000 SIMPLEX

### STANDARDS

•ISO/IEC 11801; EN 50173-1; IEC 61754-1; IEC 61753-1; IEC 61300.



### OPERATING PERFORMANCE

Singlemode


	UPC	APC
Insertion Loss (dB)	< 0.3	< 0.3
Durability (500 Mating) (dB)	< 0.2	< 0.2
Operation Temperature (°C)	-40 to 85	-40 to 85
Retention Force (N)	200-600	200-600
Housing Material	PEI	PEI
Mounting Style	Screws	Screws
Sleeve Material	Ceramics (Grade A)	Ceramics (Grade A)
Colour	Blue	Green

### ORDER INFORMATION


Code	Description	Conector	Category	Typology	Color	Quantity (un)
81411071050	Adapter OS2 E2000/APC Simplex	E2000/APC	OS2	Simplex	Green	1
81411081040	Adapter OS2 E2000 Simplex	E2000	OS2	Simplex	Blue	1
81411101050	Adapter OS2 E2000/APC-SC/APC Simplex	E2000/APC-SC/APC	OS2	Simplex	Green	1

### TECHNICAL DRAWING (mm)

#### B2000/APC SIMPLEX | E2000 SIMPLEX



#### B2000/APC - SC/APC SIMPLEX



As part of our goal to achieve quality excellence, our barpa System Warranty can give you 25 years products and solution assurance of compliance with the industry performance standard comparing with the class installed. This warranty applies to network infrastructure installations that was made by an approved barpa Partner using an barpa solution (end-to-end). For more informations go to our website.