ACCESSORIES FOR CRUX 3 - DATASHEET PATCH PANEL

Posted on 26-06-2024 by barpaadminuser

EMPTY PATCH PANEL
12P - 1U - 10"



DESCRIPTION

This Empty Patch Panel belongs to the barpa cabling system. It accepts connectors from category 6 to 6A, UTP and STP. For Modular Keystone.

STANDARD CONFORMITY

- EIA 10-inch

CE ROHS

PHYSICAL CHARACTERISTICS

Chassis	Black Electrostatic Powder-Coated Steel: phosphor bronze with tin plating over nickel
Color	Black (RAL9005)
Plastic	Fire self-extinguish high impact plastic

ELECTRICAL CHARACTERISTICS

Contact Resistance (MΩ)	200
Insulation Resistance (MΩ Min 500V DC)	500
Withstand Voltage	DC 1000V AC 700V RMS 60Hz, 1min

ENVIRONMENTAL CONDITIONS

Operating Temperature (°C)	-10 a +60
Storage Temperature (°C)	-40 a +70

LOGISTICS INFORMATION

		Inner Box		Carton		
Code	Unit Weight (kg)	Size (mm)	Quantity (un)	Size (mm)	Quantity (un)	EAN Code
82330601112	0,27	265x125x55	1	520x260x300	18	5608445014160

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu