

ANGLED PATCH PANEL EMPTY – 24 PORTS – 1U - DATASHEET

Posted on 20-03-2025 by barpaadminuser

barpa

ANGLED PATCH PANEL
EMPTY 24 PORTS 1U

DESCRIPTION

The Angled 19" 1U 24-Port Empty Panel is quick and easy to install. It features a rear cable retention system with adjustable mechanical regulation, eliminating the need for the traditional serrated tie fixing system. It includes a label holder with plastic protection for identifying RJ45 ports and a ground drain connection.



APPLICABLE STANDARDS

• ISO/IEC 11801 ed.2.2 • EN 50173-1 • ANSI/TIA 568-B.2-1 • EIA 19-inch



PHYSICAL CHARACTERISTICS

Material	Chassis	Black Electrostatic Powder-Coated Steel; phosphor bronze with tin plating over nickel.
	Plastic	Fire self-extinguish high impact plastic
Color	Black (RAL9005)	
Dimensions (mm)	481,12x44,16x181,24	
Unit Weight (kg)	0,5523	
Number of Ports	24	
Keystones Jack	STP and UTP	

ELECTRICAL CHARACTERISTICS

Contact Resistance (MΩ)	200
Insulation Resistance (MΩ Min 500V DC)	500
Withstand Voltage	DC 1000V AC 700V RMS 60Hz, 1min

ENVIRONMENTAL CONDITIONS

Operating Temperature (°C)	-10 to +60
Storage Temperature (°C)	-40 to +70

MECHANICAL SPECIFICATIONS

Cable OD (mm)	5,0 - 8,5
---------------	-----------

This document is authored and owned by barpa. It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu
datasheet n° b185_0 | date: 03/25
approved by: Ana Barbosa

