ANGLED PATCH PANEL EMPTY – 24 PORTS – 1U - DATASHEET

Posted on 20-03-2025 by barpaadminuser

ANGLED PATCH PANEL EMPTY 24 PORTS 1U

DESCRIPTION

The Angled 19" 1U 24-Port Empty Panel is quick and easy to install. It features a rear cable retention system with adjustable mechanical regulation, eliminating the need for the traditional serrated tie fixing system. It includes a label holder with plastic protection for identifying RJ45 ports and a ground drain connection.



APPLICABLE STANDARDS

• ISO/IEC 11801 ed.2.2 • EN 50173-1 • ANSI/TIA 568-B.2-1 • EIA 19-inch

PHYSICAL CHARACTERISTICS

Material	Chassis	Black Electrostatic Powder-Coated Steel: phosphor bronze with tin plating over nickel.
	Plastic	Fire self-extinguish high impact plastic
Color		Black (RAL9005)
Dimensions (mm)		481,12x44,16x181,24
Unit Weight (kg)		0,5523
Number of Ports		24
Keystones Jack		STP and UTP

ENVIRONMENTAL CONDITIONS

Operating Temperature (°C)	-10 to +60
Storage Temperature (°C)	-40 to +70

MECHANICAL SPECIFICATIONS

Cable OD (mm)	5,0 - 8,5

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu