CABLE CAT.6 U/FTP LSZH – 23AWG - DATASHEET

Posted on 26-06-2024 by barpaadminuser

ENTERPRISE/DATA CENTER COPPER CABLE
CAT6 U/FTP - LSZH - 23 AWG - 0,56mm

DESCRIPTION

Performance specified up to 250MHz and tested up to 550MHz. Decreasing length cable markings - Easy identification of remaining cable reduces installation time and cable scrap. Designed to Support all Class E protocols including 1GBASE-T. Support PoE, voice, video and Gigabit Ethernet.





25 YEARS WARRANTY · LSZH · INDOOR · 23 AWG · ROHS · CE · CPR Dca

APPLICABLE STANDARDS

Electrical Performance
• ISO/IEC 11801 • ISO/IEC 61156-5 • EN 50173 • EN 50288-5-1
• ANSI/ TIA-568-D

Reaction to fire
• IEC 60332-3-22 • IEC 60754 • IEC 61034 • EN 50267-2-3 • EN 13501-6
• EN ISO 1716:2010 • EN 50575;

PoE
• IEEE 802.3bt PoE Type 1, 2, 3 and 4

CABLE PROPERTIES

Category		CAT6 U/FTP		
Conductor	Material	Copper		
	Nom O.D.	0,56 ± 0,005 mm		
		0,022 in		
Insulation	Material	Skin-foam-skin PE		
	Diameter	1,330 ± 0,05 mm		
		0,052 in		
Sheath	Thickness	0,55 ± 0,05 mm		
		0,022 in		
	External O.D.	7,3 ± 0,4 mm		
		0,287 ± 0,015 in		
	Material	LSZH (complies RoHS)		
	Color	Purple (RAL4005)		
Rip-cord		Yes		
Core Color	Pair 1	White & Blue / Blue	Pair 2	White & Orange / Orange
	Pair 3	White & Green / Green	Pair 4	White & Brown / Brown

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu