CABLE CAT.6A S/FTP PE – 23AWG - DATASHEET

Posted on 26-06-2024 by barpaadminuser

ENTERPRISE/DATA CENTER COPPER CABLE
CAT6A S/FTP - PE - 23 AWG - 0,56mm

DESCRIPTION

Performance specified up to 500MHz. Individual foil pairs with external S foil. Decreasing length cable markings - Easy identification of remaining cable reduces installation time and cable scrap. Designed to Support all Class EA protocols including 10GBASE-T. Supports Power Over Ethernet (PoE), Power Over Ethernet Plus (PoE+), High Power Ethernet (PoE++) and 4 Pair Power Over Ethernet (4PPoE) Applications.





1. Aluminum Foil
2. Braid
3. Drain Wire
4. Rip-cord
5. Outer Jacket

UV RESISTANT · HALOGEN FREE · 25 YEARS WARRANTY · PE · OUTDOOR · 23 AWG · ROHS · CE

APPLICABLE STANDARDS

Electrical Performance:

• ISO/IEC 11801 • ISO/IEC 61156-5 • EN 50173 • EN 50288-10-1
• ANSI/ TIA-568-D.2

PoE:

• IEEE 802.3bt PoE Type 1, 2, 3 and 4.

CONSTRUCTION

Category		CAT6A S/FTP		
Conductor	Material	Solid Bare Copper		
	Nom O.D.	0,56 ± 0,005 mm		
		0,022 in		
Insulation	Material	Skin-foam-skin PE		
	Diameter	1,330 ± 0,05 mm		
		0,052 in		
Sheath	Thickness	0,55 ± 0,05 mm		
		0,022 in		
	External O.D.	7,6 ± 0,5 mm		
		0,307 ± 0,019 in		
	Material	LDPE (complies RoHS)		
	Color	Black (RAL9005)		
Rip-cord		Yes		
Core Color	Pair 1	White & Blue / Blue	Pair 2	White & Orange / Orange
	Pair 3	White & Green / Green	Pair 4	White & Brown / Brown

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu