CABLE CAT.6A U/FTP LSZH – 23AWG – 700 MHZ - DATASHEET

Posted on 26-06-2024 by barpaadminuser

ENTERPRISE/DATA CENTER COPPER CABLE
CAT6A U/FTP - LSZH -23 AWG - 0,56mm - 700MHz

DESCRIPTION

Performance tested up to 700MHz in independent lab Force Technology. Individual foil pairs. Decreasing length cable markings - Easy identification of remaining cable reduces installation time and cable scrap. Designed to Support all Class EA protocols including 10GBASE-T. Supports Power Over Ethernet (PoE), Power Over Ethernet Plus (PoE+), High Power Ethernet (PoE++) and 4 Pair Power Over Ethernet (4PPoE) Applications.





1. Drain Wire
2. Rip-cord
3. Aluminum Foil
4. Outer Jacket
5. Insulation
6. Conductor

25 YEARS WARRANTY · 700MHz · INDOOR · 23 AWG · ROHS · CE · CPR C_{CA} / D_{CA}

APPLICABLE STANDARDS

Electrical Performance:
- ISO/IEC 11801 - ISO/IEC 61156-5 - EN 50173 - EN 50288-10-1
- ANSI/ TIA-568-D.2;

Reaction to fire:
- IEC 60332-3-22 - IEC 60754 - IEC 61034 - EN 50267-2-3 - EN 13501-6
- EN ISO 1716:2010 - EN 50575

PoE:
- IEEE 802.3bt PoE Type 1, 2, 3 and 4

CONSTRUCTION

Category		CAT6A U/FTP 700MHz		
Conductor	Material	Solid Bare Copper		
	Nom O.D.	0,56 ± 0,005 mm		
		0,022 in		
Insulation	Material	Skin-foam-skin PE		
	Diameter	1,330 ± 0,05 mm		
		0,052 in		
Sheath	Thickness	0,55 ± 0,05 mm		
		0,022 in		
	External O.D.	7,4 ± 0,5 mm		
		0,307 ± 0,019 in		
	Material	LSZH (complies RoHS)		
	Color	Purple (RAL4005)		
Rip-cord		Yes		
Core Color	Pair 1	White & Blue / Blue	Pair 2	White & Orange / Orange
	Pair 3	White & Green / Green	Pair 4	White & Brown / Brown

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu

datasheet nº b5_8 | date: 04/25
approved by: Ana Barbosa