CABLE CAT.7 S/FTP LSZH – 23AWG - DATASHEET


Posted on 26-06-2024 by barpaadminuser

ENTERPRISE/DATA CENTER COPPER CABLE
CAT7 S/FTP - LSZH - 23 AWG - 0,56mm

DESCRIPTION

Performance specified up to 600MHz and tested up to 1000MHz. Individual foil pairs with external S foil. Decreasing length cable markings - Easy identification of remaining cable reduces installation time and cable scrap. Designed to Support all Class F protocols including 10GBASE-T. Supports Power Over Ethernet (PoE), Power Over Ethernet Plus (PoE+), High Power Ethernet (PoE++) and 4 Pair Power Over Ethernet (4PPoE) Applications.





1. Outer Jacket
2. Rip-cord
3. Al/Mylar
4. Braid
5. Drain wire

APPLICABLE STANDARDS

Electrical Performance:
• ISO/IEC 11801 • ISO/IEC 61156-5 • EN 50173 • EN 50288-4-1 ANSI/ TIA-568-D.2

Reaction to fire:
• IEC 60332-3-22 • IEC 60754 • IEC 61034 • EN 50267-2-3 • EN 13501-6
• EN ISO 1716:2010 • EN 50575

PoE:
• IEEE 802.3bt PoE Type 1, 2, 3 and 4.

25 YEARS WARRANTY · LSZH · INDOOR · 23 AWG · ROHS · CE · CPR C_{CA}

CONSTRUCTION

Category		CAT 7 S/FTP		
Conductor	Material	Solid Bare Copper		
	Nom O.D.	0,56 ± 0,005 mm		
		0,022 in		
Insulation	Material	Skin-foam-skin PE		
	Diameter	1,330 ± 0,05 mm		
		0,052 in		
Sheath	Thickness	0,55 ± 0,05 mm		
		0,022 in		
	External O.D.	7,8 ± 0,5 mm		
		0,307 ± 0,019 in		
	Material	LSZH (complies RoHS)		
	Color	Orange (RAL2003)		
Rip-cord		Yes		
Core Color	Pair 1	White & Blue / Blue	Pair 2	White & Orange / Orange
	Pair 3	White & Green / Green	Pair 4	White & Brown / Brown

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu