DISTRIBUTION BOX FOR 24 FIBERS - DATASHEET

Posted on 25-06-2024 by barpaadminuser

DISTRIBUTION BOX 24 FIBERS

DESCRIPTION

barpa Distribution Box is used in FTTH access network and accomodates 24 fibers. Suitable for inside or outside applications, with the function of mechanical splice or fusion, was designed to enlarge fiber capacity and save cost. With a waterproof, dust-proof and wet-proof design, has a total enclosed structure.

ROHS

SPECIFICATIONS

Material	ABS/PC
Color	Grey
IP	55
Dimensions (mm)	265x155x54
Applicable Environment	Indoor or Outdoor
Installation	Wall Mounting
Operating Temperature (oC)	-40 to 85
Weight (kg)	0,650

ACESSORIES INCLUDED

Two pre-installed splice cassette
6 small cable ties
4 cage nut fixing set
Screw lock

LOGISTICS INFORMATION

		Inner Box		Outer Box	
Code	Unit Weight (kg)	Dimensions (mm)	Quantity (un)	Dimensions (mm)	Quantity (un)
81602020240	0,650	277x167x61	1	580x355x36	20

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu