FIBER OPTIC DIN RAIL BOX - DATASHEET

Posted on 28-08-2024 by barpaadminuser

FIBER OPTIC DIN RAIL BOX

DESCRIPTION

barpa's Fiber Optic DIN Rail Box is designed typically for industrial environments that demand robust and reliable solutions. This box provides distribution and terminal connections for a variety of optical fiber systems where optical cables, patch cords, or pigtails need to be efficiently connected in limited spaces. With a compact design, this box can be used with different ports and offers secure cable entries and an integrated fiber optic splice tray. This product helps you to ensure performance and durability in demanding environments.



ROHS

25 YEARS WARRANTY

APPLICABLE STANDARDS

• Directive 2011/65/EU (RoHS) • IEC 60715 • TIA/EIA-568 • ISO/IEC 11801
• ANSI/TIA-568.3-D

TECHNICAL CHARACTERISTICS

Dimensions (mm)	130 x 132 x 35
Material	SPCC Steel
Thickness (mm)	1,2
Weight (kg)	0,593
Color	Light Grey (RAL 7035)
Temperature Range (°c)	-40 to 80
Cable Entries	2 x M20
Splice Tray	Yes
Front Plates*	12 SC Simplex or 12 LC Duplex (for adapters without Flanges) 8 SC Simplex or 8 LC Duplex 6 SC Duplex or 6 LC Quadriplex 6 ST

* Adapters and Pigtails are not included.

INCLUDED ACCESSORIES

12 x Fiber Optic Splice Sleeves 2,8mm - 40mm

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu

datasheet nº b169_2 | date: 12/25
approved by: Ana Barbosa