FIBER OPTIC SLIDING PATCH PANEL - DATASHEET

Posted on 25-06-2024 by barpaadminuser

FIBER OPTIC PATCH PANEL WITH CABLE MANAGEMENT



DESCRIPTION

barpa Fiber Optic Patch Panel with cable management is a standard 19''. Supplied with pre-configured front panel for fast and easy installation. With a high quality material, transparent cover and a good dust-proof, it´s used for manage optical fiber terminations and splices up to 48 fibers in 1U of rack space. With a sliding drawer design for easy access and with cable management and front cover, the panel are available in black colour.

APPLICABLE STANDARDS

- EIA 19-inch

ROHS

FEATURES

Adapter Type	SC Duplex / SC Simplex
Thickness (mm)	1,2
Material	Steel
Color	Black (RAL9005)
Dimension (mm)	483x303x46
Admissible Quantity of Splice Cassettes	4
Number of Splices per Cassete	12
Weight (kg)	4,6
Max Diameter of Cable (mm)	22

ACESSORIES INCLUDED

One pre-installed splice cassette
6 small cable ties
Stick with fiber attention
12 Black covers for unused port

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning it's authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are mainly illustrative.
More information: info@barpa.eu or in www.barpa.eu

datasheet nº b90_4 | date: 02/25
approved by: Ana Barbosa