HOOK AND LOOP FASTENER - DATASHEET

Posted on 27-06-2024 by barpaadminuser

HOOK AND LOOP FASTENER
16mm x 25m

DESCRIPTION

With this solution you can achieve a fast and easy application. Adjustable and reusable. Can be cut to the desired length. UV Resistant. Logo in every 20cm.



SPECIFICATIONS

Colour	Black with white logo
Hook Material	Nylon
Loop Material	Polyester
Base Material	Synthetic Resin
Hook Melt Temperature	230ºC
Loop Melt Temperature	180ºC
Working Temperature	-40ºC to 85ºC
Min. Installation Temperature	-20ºC
Water resistant	Can be used underwater, consider that tensile will reduce in 50%, after dry, it will recover
Chemical resistant	Alkaline Sode (50%); Ammonia (28%); Hydrochlori Acid (2,5%); Nitric Acid (3,5%)
Tensile Strength	25N || 5,6lb
Peeling Force	3N || 0,67lb
*Remark: The tensile strength and durability will be reduced under cold temperatures.	

ORDER INFORMATION

	Paper Tape			Inner Box			Outer Box		
Code	Width (mm)	Unit Weight (kg)	Quantity (un)	Dimensions (mm)	Weight (kg)	Quantity (un)	Dimensions (mm)	Weight (kg)	Quantity (un)
82391511025	350	0,23	1	240x240x180	2,6	10	500x260x200	5,8	20

LOGISTIC INFORMATION

This images are merely illustratives. We want you to see the importance we attach to the packaging.
We always work with products and materials that are easy to use.



This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu