MULTITUBE CABLE WITH CORRUGATED STEEL 1800N – DOUBLE SHEATH – LSZH - DATASHEET

Posted on 25-06-2024 by barpaadminuser

LOOSE TUBE MULTITUBE CABLE CORRUGATED STEEL ARMOURING DOUBLE SHEATH 1800N LSZH



DESCRIPTION

For indoor and/or outdoor installations. Mostly used in telecom trunk lines, CATV trunk lines. For direct burial and for cases of high risk of rodent attacks.



1. Filler
2. Water-blocking Yarn
3. Loose Tube
4. Colored Coating Fiber
5. Filling Gel
6. Central Strenght Member
7. Waterproof Tape
8. Binding Yarn
9. Inner Jacket
10. Corrugated Steel
11. Outer Jacket

APPLICABLE STANDARDS

• EN 187 000 • IEC 60794-3 • IEC 60794-3-10
• IEC 60794-3-12 • ISO 11801 • EN 50 173-1 • IEC 60793-2-50
• IEC 60793-2-10 • IEC 60794-1-21 • IEC 60794-1-22



CABLE PROPERTIES

Coating Fiber	Color	1 - red	1 - red with mark
		2 - green	2 - green with mark
		3 - blue	3 - blue with mark
		4 - yellow	4 - yellow with mark
		5 - white	5 - white with mark
		6 - grey	6 - grey with mark
		7 - brown	7 - brown with mark
		8 - violet	8 - violet with mark
		9 - turquoise	9 - turquoise with mark
		10 - black	10 - black with mark
		11 - orange	11 - orange with mark
		12 - pink	12 - pink with mark
Loose Tube	Dimension (mm)	2,3	
Water Blocking		Tape	
Central Strenght member	Material	2,5mm FRP rod	
Ripcord		1 rip cord	
Armouring	Material	Corrugated steel 0,15mm	
Sheath	Material	1,5mm MDPE	
	Color	Black	
	Marking	(code) barpa FO Multi w Corrugated Steel LSZH Double (fiber type) (No of fibers)F (batch no.) Made in EU (meters)m	
VDE 888		V-DQH(SR)H	

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu