

OPEN RACK - PYXIS 1 - DATASHEET

Posted on 26-06-2024 by barpaadminuser





SERIES PYXIS 1

DESCRIPTION

barpa Pyxis 1 cabinet was designed for network rooms with low ventilation. It's available in a range of heights and accommodates a load of up to 250 kg. The best way to get the most of this cabinetis with barpa accessories, you should get them separately. Order this product either assembled or in flat packs. Order this product either assembled or in flat packs.

APPLICABLE STANDARDS

• EN60603-7-51 • IEEE 802.3at • ANSI/TIA-568-D













SPECIFICATIONS

Material	SPCC Cold Rolled Steel; Column: 1.5mm. Others 2.0mm		
Loading Capacity (kg)	250		
Color	Black (RAL9004)		
Ventilation (%)	100		
Product Family	Series Pyxis		

FEATURES

Modular design, easily assemble and disassemble for delivery, low-cost

Many optional accessories according to requirements (cable management slot, removable working panel, etc.)

ORDER INFORMATION

					Dimensions (mm)	Weight (kg)
Code	U	Width (mm)	Width (mm)	Mounted Height (mm)	Pack 1	Pack 1
82331290606	29			1288	1420x280x140	30
82331330606	33			1660	1600x280x140	32
82331380606	38	600	600	1822	1820x280x140	35
82331420606	42	_		2000	2000x280x140	36
82331470606	47	_		2222	2220x280x140	40

Note: To order the assembled rack, add "M" at the end of the code.

This document is authored and owned by loops . It is forbidden to reproduce in whole or in part without mentioning its authoriship, as well as madification of its content or context. All specifications are subject to change without notice.

The pickness drawings are merely illustrative.

Whose informations in infanchia.

datasheet n° b39_4| date: 01/25

