PATCH CORD OS2 G652D - DATASHEET

Posted on 25-06-2024 by barpaadminuser

PATCH CORD
OS2 G652D

DESCRIPTION

High performance and strong design. High quality connectors; Individually packed. Available with yellow outer jacket. Dust protection caps and cable boots included. Duplex clip in SC, LC and E2000 connector, ST and FC connector without clip.


ST DUPLEX


LC DUPLEX


SC DUPLEX


SC/APC DUPLEX


LC-SC/APC DUPLEX


LC-ST DUPLEX


LC-SC DUPLEX


E2000/APC DUPLEX

APPLICABLE STANDARDS

• ISO/IEC 11801 • EN 50173-1 • IEC 61754-20 • IEC 61753-1
• IEC 61300 • RoHS

ROHS LSZH 25 YEARS WARRANTY

CONNECTOR PROPERTIES

	ST	SC	LC	SC/APC	E2000/APC
Insertion Loss (dB)	< 0,2	< 0,2	< 0,2	< 0,2	< 0,2
Return Loss (dB)	> 50	> 50	> 50	> 60	> 60
Fiber Ferrule (mm)	Ceramic 2,5	Ceramic 2,5	Ceramic 1,25	Ceramic 2,5	Ceramic 2,5
Connector Housing	Bronze	Composite	Composite	Composite	Composite
Connector Design	EC60874-10-1997	IEC61754-4	IEC61754-20	IEC61754-4	-

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are mainly illustrative.
More information: info@barpa.eu or in www.barpa.eu