PATCH CORD OS2 G657A2 STAGGERED - DATASHEET

Posted on 25-06-2024 by barpaadminuser

PATCH CORD OS2 G657A2 STAGGERED ON ONE SIDE

DESCRIPTION

High performance and strong design, these patch cords are staggered on one side for easy installation. High quality connectors; Individually packed. Available with yellow outer jacket. Dust protection caps and cable boots included, both green. Duplex clip in SC.



APPLICABLE STANDARDS

• ISO/IEC 11801 • EN 50173-1 • IEC 61754-20 • IEC 61753-1
• IEC 61300 • EN 60794-1-1 • EN 60793-2-50 • RoHS

CPR Dca -s2,d2,a1 · CE · ROHS · LSZH · 25 YEARS WARRANTY

CONNECTOR PROPERTIES

	SC/APC
Insertion Loss (dB)	< 0,2
Return Loss (dB)	> 60
Fiber Ferrule (mm)	Ceramic 2,5
Connector Housing	Composite
Connector Design	IEC61754-4

CABLE PROPERTIES

	SC/APC
Attenuation (dB/km @ 1310nm)	0,4
Attenuation (dB/km @ 1550nm)	0,3
Radius of Curvature (mm)	5≤r≤12
Fiber Height (nm)	-100≤h≤100
Durability	500 times
Repetitiveness (dB)	≤ 0,2
Number of Fibers	2
Weight (kg/km)	15
Outer Diameter WxH (mm)	3,00x2
Outer Sheath Colour	Yellow
Outer Sheath Material	LSZH

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu