PATCH PANEL - CAT.6 UTP IDC 180° – 24 PORTS – 1U - DATASHEET

Posted on 27-06-2024 by barpaadminuser

PATCH PANEL CAT6 UNSHIELDED 24 PORT 1U IDC 180º



DESCRIPTION

The barpa Category 6 UTP (Unscreened Twisted Pair) patch panel belongs to the barpa cabling system. Suitable for both 110 & Krone Punchdown Tool. Has a very special design with a rear cable retention system with ajustable mechanical ajustment, that promotes quick installation and fast termination, avoiding the traditional fastening system by cable tie. Supports all applications up to 250Mhz. Manufactured and tested to the latest Category 6 specifications defined in the Internacional standards.

APPLICABLE STANDARDS

• IEC 60603-7-41 • IEC 60512-26-100 • ISO/IEC 11801 ed.2.2
• EN 50173-1 • ANSI/TIA 568-B.2-1

POE

• IEEE 802.3bt PoE Type 1, 2, 3 e 4

FEATURES

Compatibility with CAT6 and lower classes
25 Years System Warranty
High-density 1U
1 Gigabit Ethernet
For 110 & Krone Punchdown Tool

PHYSICAL CHARACTERISTICS

Chassis	Black Electrostatic Powder-Coated Steel: phosphor bronze with tin plating over nickel
Color	Black (RAL9005)
Plastic	Fire self-extinguish high impact plastic

ELECTRICAL CHARACTERISTICS

Contact Resistance (MΩ)	200
Insulation Resistance (MΩ Min 500V DC)	500
Withstand Voltage	DC 1000V AC 700V RMS 60Hz, 1min

ENVIRONMENTAL CONDITIONS

Operating Temperature (°C)	-10 to +60
Storage Temperature (°C)	-40 to +70

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu