

PATCH PANEL – EMPTY – 24 PORTS - DATASHEET 0.5U

Posted on 27-06-2024 by barpaadminuser



PATCH PANEL FOR
24 KEYSTONES RJ45 - 0,5U

DESCRIPTION

This Empty Patch Panel belongs to the barpa cabling system. It accepts connectors from category 6 to 6A, UTP and STP. Has a very special design with a rear cable retention system with ajustable mechanical ajustment, that promotes quick installation and fast termination, avoiding the traditional fastening system by cable tie. Includes tag holder with plastic protection for identification of RJ 45, also with earth connection. For Modular Keystone.



APPLICABLE STANDARDS

- EIA 19-inch

PHYSICAL CHARACTERISTICS

Chassis	Black Electrostatic Powder-Coated Steel: phosphor bronze with tin plating over nickel
Color	Black (RAL9005)
Plastic	Fire self-extinguish high impact plastic

ELECTRICAL CHARACTERISTICS

Contact Resistance (MΩ)	200
Insulation Resistance (MΩ Min 500V DC)	500
Withstand Voltage	DC 1000V AC 700V RMS 60Hz, 1min

ENVIROMENTAL CONDITIONS

Operating Temperature (°C)	-10 to +60
Storage Temperature (°C)	-40 to +70

MECHANICAL SPECIFICATIONS

Cable OD (mm)	5.0 - 8.5
---------------	-----------

This document is authored and owned by barpa. It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu
datasheet n° b23_2 | date: 01/25
approved by: Ana Barbosa

