PIGTAIL OM1 62.5/125 - DATASHEET

Posted on 25-06-2024 by barpaadminuser

PIGTAIL MULTIMODE OM1 62,5/125

DESCRIPTION

High performance and strong design. High quality connectors; Individually packed. Available with orange outer jacket. Dust protection cap and cable boot included. Provides a fast way to make factory terminations in the field.



SC SIMPLEX



ST SIMPLEX



LC SIMPLEX

APPLICABLE STANDARDS

• ISO/IEC 11801 • EN 50173-1 • IEC 61754-20 • IEC 61753-1 • IEC 61300 • RoHS

CE ROHS LSZH 25 YEARS WARRANTY

CONNECTOR PROPERTIES

	ST	SC	LC
Insertion Loss (dB)	< 0,2	< 0,2	< 0,2
Return Loss (dB)	> 25	> 25	> 25
Fiber Ferrule (mm)	Ceramic 2,5	Ceramic 2,5	Ceramic 1,25
Connector Housing	Bronze	Composite	Composite
Connector Design	EC60874-10-1997	IEC61754-4	IEC61754-20

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are mainly illustrative.
More information: info@barpa.eu or in www.barpa.eu