PIGTAIL OS2 G657B3 - DATASHEET

Posted on 25-06-2024 by barpaadminuser

PIGTAIL SINGLEMODE OS2 G657B3

DESCRIPTION

High performance and strong design. High quality connectors. Individually packed. Available with yellow outer jacket. Dust protection cap and cable boot included. Provides a fast way to make factory terminations in the field.

APPLICABLE STANDARDS

• ISO/IEC 11801 • EN 50173-1 • EN 60793 • IEC 61754-20
• IEC 61753-1 • IEC 61300 • RoHS



LC



ST SIMPLEX



ST SIMPLEX



ST SIMPLEX



ST SIMPLEX

CE ROHS LSZH 25 YEARS WARRANTY

CONNECTOR PROPERTIES

	LC	ST	SC	FC	SC/APC
Insertion Loss (dB)	< 0,2	< 0,2	< 0,2	< 0,2	< 0,2
Return Loss (dB)	> 50	> 50	> 50	> 50	> 60
Fiber Ferrule (mm)	Ceramic 1,25	Ceramic 2,5	Ceramic 2,5	Ceramic 2,5	Ceramic 2,5
Connector Housing	Composite	Bronze	Composite	Bronze	Composite
Connector Design	IEC 61754-20	EC60874-10-1997	IEC61754-4	IEC61754-13	IEC61754-4

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning it's authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are mainly illustrative.
More information: info@barpa.eu or in www.barpa.eu