

SAFETY BEAM SENSOR

Posted on 01-07-2026 by barpaadminuser



SAFETY BEAM SENSOR

DESCRIPTION

The ML29 Safety Light Curtain offers fast and reliable detection up to 8,5 m, with simple installation using adhesive strips or screws. The wide beam angle makes alignment easy and allows for multi-beam configuration for enhanced protection.



*BirSens brand product integrated into the ORION solution

KEY FEATURES

Single-beam monitoring with an extremely narrow sensor
Easy installation (Plug&Play)
Ideal for installation on door frames or profiles
"Dark on" version (activates when the beam is interrupted)

PHYSICAL AND MECHANICAL CHARACTERISTICS

Code	8244 0205001
Dimensions (mm)	85,2x11,6x9,2
Weight (g)	12
Degree of Protection	IP65
Cable Length (m)	6
Light Source	Infrared

ELECTRICAL SPECIFICATIONS

Threshold Detection Range (m)	8,5	
Operating Voltage	11 - 30V DC	
No-load Supply Current	Emitter	≤ 25 mA
	Receiver	≤ 10 mA
Transmitter Disable Signal Input	+UB ≤ 5V	
Signal Output	Short-circuit protected, reverse polarity protected	
Maximum Switching Voltage	30V DC	
Maximum Switching Current	0,1A	
Switching Frequency	100 Hz	
Response Time	5 ms	

This document is authored and owned by barpa. It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice. The pictures/drawings are merely illustrative. More information: info@barpa.eu or in www.barpa.eu
datasheet n° b229_0 | date: 05/26
 approved by: Ana Barbosa

