

SERVER CABINET - CETUS 1 - DATASHEET

Posted on 25-06-2024 by barpaadminuser



CETUS 1 CABINET

DESCRIPTION

Cetus 1 cabinet was designed for demanding spaces, like Data Centers. It's available in a range of heights and depths and accommodate a load of up to 1500 kg. The best way to get the most of this cabinet is with barpa accessories, you should ask them separately. Order this product either assembled or in flat packs.



SPECIFICATIONS

Standard	ANSI/EIA RS-310-D; IEC60297-2; DIN41494 Part 1 and 7
Material	SPCC Cold Rolled Steel; 19" rails: 2.0mm; Casters tray: 2.0mm; Others 1.2mm
Loading Capacity (kg)	1500
Color	Black (RAL9004)
Ventilation (%)	67
Earth connection	Yes
Product Family	Series Cetus
Packaging	Cetus cabinets are shipped in disassembled packing, saving transportation and storage cost
Design	Side door: split into 2 parts, lockable with square locks; Front and rear door; Pluggable front door and rear doors, with external hinges. Casters: Built-in installation design
Frame	Duplex profile frames, could be connected by 8 pieces of screws
Front and rear doors	Sheet steel front door perforated + Double sheet steel rear door perforated
Cable entries on top and bottom	Sliding and adjustable cable entries on top and bottom, edges of cable entries are with the design to prevent wires from scratching
Mounting rails	Installation position of mounting rails could be adjusted quickly
Includes	2 x vertical cable management panel. Locks. Casters. Adjustable feet.

This document is authored and owned by barpa. It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu
datasheet n° b33_4 | date: 01/25
approved by: Ana Barbosa

