ULTRA HIGH DENSITY PATCH PANEL - DATASHEET

Posted on 25-06-2024 by barpaadminuser

FIBER OPTIC
ULTRA HIGH DENSITY PATCH PANEL

DESCRIPTION

barpa UHD Fiber Optic Patch Panel is a standard 19''. It´s used to manage optical fibers up to 144 fibers in 1U of rack space. It's modular design makes it easier to use for different types of barpa UHD fiber cassettes. With a drawer design for easy access, this panel is available in black color and different sizes.



APPLICABLE STANDARDS

• ISO/IEC 11801 • EN 50173-1 • IEC 61754-1 • ANSI/TIA-568.3-E • EIA 19-inch







1U	2U	4U
144F MPO/MTP®-LC capacity	Capacity for 288F MPO/MTP®-LC	576F MPO/MTP®-LC capacity
Up to 18 8F barpa UHD fiber cassettes	Up to 36 8F barpa UHD fiber cassettes	Up to 72 8F barpa UHD fiber cassettes
Up to 12 12F barpa UHD fiber cassettes	Up to 24 12F barpa UHD fiber cassettes	Up to 48 12F barpa UHD fiber cassettes

FEATURES

Front and Rear Cassette Entry
Enables 8F and 12F applications with maximum panel density
Adjustable mounting brackets with open holes for easy installation
Innovative Design
Front and Rear Cable Management
Ready for future applications: duplex and parallel fiber systems

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning it's authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu