UNITUBE CABLE WITH GLASS YARN 1200N – PE - DATASHEET

Posted on 18-07-2024 by barpaadminuser

UNITUBE FIBER OPTIC CABLE WITH GLASS YARNS 1200N PE



DESCRIPTION


For outdoor installations. Easy and fast installation due to its small diameter and light construction. Suitable for pushing, blowing method. Problem-free use in power lines due to its non-metallic construction. Mostly used in campus backbone applications. In network systems, MAN, WAN, LAN applications. With a degree of rodent protection, effective in many cases.



1. Strength Member
2. Colored Coating Fiber
3. Filling Gel
4. Loose Tube
5. Outer Jacket
6. Rip-Cord

APPLICABLE STANDARDS

• ISO/IEC 11801; • EN 50173-1; • IEC 60794-1; • IEC 60793-2-50;
• IEC 60793-2-10; • IEC 60794-1-21; • IEC 60794-1-22;



CABLE PROPERTIES

Coating Fiber	Color	1 - Blue	13 - Blue
		2 - Orange	14 - Orange
		3 - Green	15 - Green
		4 - Brown	16 - Brown
		5 - Gray	17 - Gray
		6 - White	18 - White
		7 - Red	19 - Red
		8 - Black	20 - Black
		9 - Yellow	21 - Yellow
		10 - Violet	22 - Violet
		11 - Pink	23 - Pink
		12 - Aqua	24 - Aqua
		Each set of 12 fibers is grouped into a bundle	
Strenght member	Material	Waterblocked Glass Yarns	
Outer Sheath	Material	UV stabilized polyethylene (HDPE)	
	Color	Black	
	Dimension (mm)	Core Count	
		2, 4, 6, 8, 12 fibers	24 fibers
		7,1	8,0
	Marking	(code) barpa FO Unitube w Glass Yarn TS12 PE (fiber category) (No of fibers)F (batch no.) (meters)m	
Ripcord		Yes	
VDE 888		A-DQ(ZN)2Y	

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu