UNITUBE CABLE WITH GLASS YARN 3000N – PE - DATASHEET

Posted on 25-06-2024 by barpaadminuser

LOOSE TUBE UNITUBE CABLE GLASS YARN DIELECTRIC AMOURING 3000N PE

DESCRIPTION

For outdoor installations. Mostly used in campus backbone applications. With a degree of rodent protection, effective in many cases.

APPLICABLE STANDARDS

• ISO/IEC 11801 • EN 50173-1 • IEC 60794-1 • IEC 60793-2-50
• IEC 60793-2-10 • IEC 60794-1-21 • IEC 60794-1-22





1. Glass Yarns
2. Colored Coating Fiber
3. Filling Gel
4. Loose Tube
5. Outer Jacket



RODENT PROTECTION · OUTDOOR · CONDUCT · CABLE TRAY · UNDER-GROUND

CABLE PROPERTIES

Coating Fiber	Color	1 - red	1 - red with mark
		2 - green	2 - green with mark
		3 - blue	3 - blue with mark
		4 - yellow	4 - yellow with mark
		5 - white	5 - white with mark
		6 - grey	6 - grey with mark
		7 - brown	7 - brown with mark
		8 - violet	8 - violet with mark
		9 - turquoise	9 - turquoise with mark
		10 - black	10 - black with mark
		11 - orange	11 - orange with mark
		12 - pink	12 - pink with mark
Loose Tube	Dimensions (mm)	2,8	
Strength member	Material	Water-blocked Glass Yarns	
Sheath	Material	1,2mm LLDPE	
	Color	Black	
	Marking	(code) barpa FO Uni w Glass PE (fiber type) (No of fibers)F (batch no.) Made in EU (meters)m	
VDE 888		A-DQ(ZN)B2Y	

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning it's authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu