WALL MOUNTED SPLITTER DISTRIBUTION BOX - DATASHEET

Posted on 25-06-2024 by barpaadminuser

WALL MOUNTED SPLITTER DISTRIBUTION BOX

DESCRIPTION

The barpa Wall Mounted Splitter Distribution Box is designed to accommodate PLC splitters, providing an efficient solution for fiber distribution in GPON networks. The enclosure is available unloaded or ready to be tailored by HIGGS with splitters and adapters to meet project-specific requirements.



APPLICABLE STANDARDS

• ISO/IEC 11801 • EN 50173-1 • Directive 2011/65/EU (RoHS)

25 YEARS WARRANTY ROHS

KEY FEATURES

Dual-compartment design for efficient fiber management
Independent hinged covers for easy installation and maintenance
Supports flexible PLC splitter configurations up to 32 optical outputs
Optimized internal layout for organized fiber routing and protection

FEATURES

Adapter Type	SC Simplex without flange
Material	SPCC Cold Rolled Steel
Finish	Finish Powder Coating
Thickness (mm)	1,2
Color	Black (RAL9005)
Dimmension (mm)	338x196x45
Weight (kg)	2,1
Number of Way Out	32
Number of Way In	2
Applicable Environments	Interior

ACCESSORIES INCLUDED

Accessory	Quantity	Details
Expansion Screw	4	Wall mounting
Bunny Clip	4	Cable fixing clip
Cable Tie	4	-
Velcro Strap	4	-
Rubber Plug for M25 Hole	2	Ø25 mm cable entry

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice.
The pictures/drawings are merely illustrative.
More information: info@barpa.eu or in www.barpa.eu