







DESCRIPTION

The barpa Category 6 STP (Screened Twisted Pair) patch panel belongs to the barpa cabling system. Suitable for both 110 & Krone Punchdown Tool. Has a very special design with a rear cable retention system with ajustable mechanical ajustment, that promotes quick installation and fast termination, avoiding the traditional fastening system by cable tie. This shielded version gives the maximum protection from EMI/RFI interference. Supports all applications up to 250Mhz. Manufactured and tested to the latest Category 6 specifications defined in the Internacional standards.











APPLICABLE STANDARDS

• IEC 60603-7-4; IEC 60512-26-100; ISO/IEC 11801 ed.2.2; EN50173-1; ANSI/TIA 568-B.2-1

FF.	ΔΤΙ	IRFS

FEATURES
Compatibility with CAT6 and lower classes
25 Years System Warranty
High-density 1U
1 Gigabit Ethernet
For 110 & Krone Punchdown Tool

PHYSICAL CHARACTERISTICS

Chassis	Black Electrostatic Powder-Coated Steel: phosphor bronze with tin plating over nickel
Color	Black (RAL9005)
Plastic	Fire self-extinguish high impact plastic

ELECTRICAL CHARACTERISTICS

Contact Resistance (M Ω)	200	
Insulation Resistance (M Ω Min 500V DC)	500	
Withstand Voltage	DC 1000V AC 700V RMS 60Hz, 1min	

ENVIRONMENTAL CONDITIONS

Operating Temperature (°C)	-10 a +60	
Storage Temperature (°C)	-40 a +70	



MECHANICAL SPECIFICATIONS


Color Code	TIA/EIA 568A (international) and 568B (AT&T Standard) Wiring For Easy Installation		
IDC Contacts - Solid Cable	Accept 22-24 AWG solid with a insulation diameter of 0.55-0.45 mm		
IDC Contacts - Stranded Cable	Accept 22-26 AWG stranded with a insulation diameter of 0.76-0.48 mm		
Insertion Life	750 times plugging		
Plug Inforce (N)	< 30		
Cable OD (mm)	5.0 - 8.5		
Contact	Phosphor bronze		


ORDER INFORMATION - CODE

		Inner Box		Carton Box		
Code	Unit Weight (kg)	Size (mm)	Quantity (un)	Size (mm)	Quantity (un)	EAN Code
82233421124	1,39	505x120x55	1	520x260x300	10	5608445005113


TECHNICAL DRAWING (mm)

482,60





438



This document is authored and owned by barpa. It is forbidden to reproduce in whole or in part without mentioning its authorship, as well as modification of its content or context. All specifications are subject to change without notice. The pictures/drawings are merely illustrative.

More information: info@barpa.eu or in www.barpa.eu



PACKAGING

This images are merely illustratives. We want you to see the importance we attach to the packaging. We always work with products and materials that are easy to use.







As part of our goal to achieve quality excellence, our barpa System Warranty can give you 25 years products and solution assurance of compliance with the industry performance standard comparing with the class installed. This warranty applies to network infrastructure installations that was made by an approved barpa partner using an barpa solution (end-to-end). For more informations go to our website.