

DESCRIPTION

The barpa Voice Patch Panel is 19" rack mounted, available in 25 and 50 ports. Both 1U. All ports are numbered and is suitable for voice applications.

APPLICABLE STANDARDS

• ISO/IEC 11801 ed.2.2; • EN50173-1; • ANSI/TIA 568-B.2-1



FEATURES

Supplied with rack mounting kit, also with earth connection		
For 110 & Krone Punchdown Tool		
Full port labelling		

CARACTERÍSTICAS

Chassis	Black Electrostatic Powder-Coated Steel: phosphor bronze with tin plating over nickel
Color	Black (RAL9005)
Plastic	Fire self-extinguish high impact plastic

ELECTRICAL CHARACTERISTICS

Contact Resistance (M Ω)	200	
Insulation Resistance (M Ω Min 500V DC) 500		
Withstand Voltage	DC 1000V AC 700V RMS 60Hz, 1min	

ENVIRONMENTAL CONDITIONS

Operating Temperature (°C)	-10 to +60
Storage Temperature (°C)	-40 to +70

MECHANICAL SPECIFICATIONS

Color Code	TIA/EIA 568A (international) and 568B (AT&T Standard) Wiring For Easy Installation			
IDC Contacts - Solid Cable	Accept 22-24 AWG solid with a insulation diameter of 0.55-0.45 mm			
IDC Contacts - Stranded Cable	Accept 22-26 AWG stranded with a insulation diameter of 0.76-0.48 mm			
Insertion Life	750 times plugging			
Plug Inforce (N)	< 30			
Cable OD (mm)	5.0 - 8.5			
Contact	Phosphor bronze with 4-6µ" gold plating			




ORDER INFORMATION


			Inner Box		Carton	
Code	Description	Unit Weight (kg)	Size (mm)	Quantity (un)	Size (mm)	Quantity (un)
82231201125	Voice Cat 3 25 Ports 1U	1.20	505x120x55	1	520x260x300	10
82231201150	Voice Cat 3 50 Ports 1U	1.20	505x120x55	1	520x260x300	10

TECHNICAL DRAWING (mm)

82231201125



82231201150





PACKAGING

This images are merely illustratives. We want you to see the importance we attach to the packaging.

We always work with products and materials that are easy to use.



