

barpa

HOOK AND LOOP FASTENER 16mm x 25m

DESCRIPTION

With this solution you can achieve a fast and easy application. Adjustable and reusable. Can be cut to the desired length. UV Resistant. Logo in every 20cm.



SPECIFICATIONS

Colour	Black with white logo
Hook Material	Nylon
Loop Material	Polyester
Base Material	Synthetic Resin
Hook Melt Temperature	230°C
Loop Melt Temperature	180°C
Working Temperature	-40°C to 85°C
Min. Installation Temperature	-20°C
Water resistant	Can be used underwater, consider that tensile will reduce in 50%, after dry, it will recover
Chemical resistant	Alkaline Sode (50%); Ammonia (28%); Hydrochlori Acid (2,5%); Nitric Acid (3,5%)
Tensile Strength	25N 5,6lb
Peeling Force	3N 0,67lb

*Remark: The tensile strength and durability will be reduced under cold temperatures.

ORDER INFORMATION

Code	Paper Tape			Inner Box			Outer Box		
	Width (mm)	Unit Weight (kg)	Quantity (un)	Dimensions (mm)	Weight (kg)	Quantity (un)	Dimensions (mm)	Weight (kg)	Quantity (un)
82391511025	350	0,23	1	240x240x180	2,6	10	500x260x200	5,8	20

LOGISTIC INFORMATION

This images are merely illustratives. We want you to see the importance we attach to the packaging. We always work with products and materials that are easy to use.

