

#### **DESCRIPTION**

This Empty Patch Panel belongs to the barpa cabling system. It accepts connectors from category 6 to 6A, UTP and STP. Has a very special design with a rear cable retention system with ajustable mechanical ajustment, that promotes quick installation and fast termination, avoiding the traditional fastening system by cable tie. Includes tag holder with plastic protection for identification of RJ 45, also with earth connection. For Modular Keystone.









### **APPLICABLE STANDARDS**

• EIA 19-inch

## PHYSICAL CHARACTERISTICS

Chassis	Black Electrostatic Powder-Coated Steel: phosphor bronze with tin plating over nickel
Color	Black (RAL9005)
Plastic	Fire self-extinguish high impact plastic

# **ELECTRICAL CHARACTERISTICS**

Contact Resistance (M $\Omega$ )	200		
Insulation Resistance (M $\Omega$ Min 500V DC)	500		
Withstand Voltage	DC 1000V AC 700V RMS 60Hz, 1min		

# **ENVIROMENTAL CONDITIONS**

Operating Temperature (°C)	-10 to +60
Storage Temperature (°C)	-40 to +70

# **MECHANICAL SPECIFICATIONS**


Cable OD (mm) 5.0 - 8.5
-------------------------



## **ORDER INFORMATION**

		Inner Box		Carton		
Code	Unit Weight (kg)	Size (mm)	Quantity (un)	Size (mm)	Quantity (un)	EAN Code
82230101024	0.40	505x120x55	1	520x260x300	10	5608445005144

# TECHNICAL DRAWING (mm)





### **PACKAGING**

This images are merely illustratives. We want you to see the importance we attach to the packaging. We always work with products and materials that are easy to use.







As part of our goal to achieve quality excellence, our barpa System Warranty can give you 25 years products and solution assurance of compliance with the industry performance standard comparing with the class installed. This warranty applies to network infrastructure installations that was made by an approved barpa partner using an barpa solution (end-to-end). For more informations go to our website.