

CERTIFICATE OF CONSTANCY OF PERFORMANCE

1783-CPR-1568

In compliance with Regulation (EU) 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Cable Type : FO Distribution/Drop Cable

Reaction to Fire Performance: Cca, s1a, d1, a1

Cables used in buildings and other civil engineering works with the objective of limiting the generation and spread of fire and smoke

(SCOPE IS AT THE ATTACHMENT)

placed on the market under the name or trade mark of

barpa (ARGON LDA)

RUA NOE PEREIRA, 473 4510-706 FANZERES, GONDOMAR, PORTUGAL

and produced in the manufacturing plant

837

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 50575: 2014 + A1: 2016

under system 1 + for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product .

This certificate was first issued on 29.08.2025 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.



Dr. Alkan HAFÇI
Deputy Director of Directives



TÜRK STANDARDLARI ENSTİTÜSÜ

TURKISH STANDARDS INSTITUTION



ATTACHMENT OF THE CERTIFICATE OF CONSTANCY OF PERFORMANCE

PRODUCT DESCRIPTION:

Designation of cable family	FO Distribution/Drop Cable
Fiber count	2-24

RELEVANT CONSTRUCTIONAL INFORMATION:

Cable design	Tight Coated Fiber, Unfilled , Single Jacket
Single Tube / Multitube	Single tube
Concentric shield	Does not include
Armour	Does not include

**ELECTRIC CABLES-EXTENDED APPLICATION OF TEST RESULTS FOR REACTION TO FIRE
EN 50576:**

Fiber optic cable, 2-24 fibers

CABLE PARAMETER RANGE :

$$\chi = 11$$

OUTER DIAMETER RANGE :

$$D = 8,8 \text{ mm}$$



Attachment of the Certificate of Constancy of Performance, 1783-CPR-1568.