



### PRODUCT DESCRIPTION

- barpa Digital Temperature Unit has 19" standard installation. Helps control the inner temperature of the cabinet. Easy cabling and operation.

| • FEATURES                            |                            |
|---------------------------------------|----------------------------|
| Power Supply                          | 220VAC (+10%;-15%) 50/60Hz |
| Resolution (°C)                       | 1                          |
| Refrigeration Output Contact Capacity | 10A/277VAC                 |
| Power Consumption (W)                 | ≤3                         |
| Accuracy -50°C ~70°C (°C)             | ±1                         |
| Temperature Measuring Range (°C)      | -50 ~+90                   |
| Temperature Controlling Range (°C)    | -40 ~+50                   |
| Operation Temperature (°C)            | -30 ~ +75                  |
| Safe Level (IP)                       | 65                         |
| Operation Humidity (%)                | 20 ~ 85 (no condensate)    |
| Color                                 | Black                      |

| • ORDER INFORMATION |                   |                  |            |               |             |               |
|---------------------|-------------------|------------------|------------|---------------|-------------|---------------|
| Code                | Input Connector   | Unit Weight (Kg) | Inner Box  |               | Carton      |               |
|                     |                   |                  | Size (mm)  | Quantity (un) | Size (mm)   | Quantity (un) |
| 82390601210         | UK (BS1363)       | 1.95             | 510x205x65 | 1             | 650x530x180 | 10            |
| 82390601110         | German (DIN49441) |                  |            |               |             |               |
| 82390601310         | US (NEMA 5-15P)   |                  |            |               |             |               |

### TECHNICAL DRAWING (mm)

