



FIBER OPTIC PATCH PANEL

DESCRIPTION

barpa Fiber Optic Patch Panel is a standard 19". Supplied with pre-configured front panel for fast and easy installation. It's used for manage optical fiber terminations and splices up to 48 fibers in 1U of rack space. With a drawer design for easy access and adjustable in depth, the panel are available in black colour.



STANDARDS

• EIA 19-inch.



FEATURES

Adapter Type	SC Duplex / SC Simplex / ST Simplex
Thickness (mm)	1.5
Material	Steel
Color	Black (RAL9005)
Dimension (mm)	487x236x43
Admissible Quantity of Splice Cassette	4
Number of Splices per Cassete	12
Weight (kg)	3
Max Diameter of Cable (mm)	22
Durability	Min. 500 Insertions

ACCESSORIES INCLUDED

One pre-installed one splice cassette
6 small cable ties
Stick with fiber attention
2 cable glands (one big and one small)
4 cage nut fixing set
12 black covers for unused port

This document is authored and owned by barpa . It is forbidden to reproduce in whole or in part without mentioning its authorship , as well as modification of its content or context. All specifications are subject to change without notice. The pictures/drawings are merely illustrative.

More information: info@barpa.eu or in www.barpa.eu

datasheet n° b82_2

ORDER INFORMATION

Code	Description	Capacity (Fibers)	Unit Weight (kg)	Inner Box		Carton Box	
				Size (mm)	Quantity (un)	Size (mm)	Quantity (un)
815010101	Patch Panel for 24 SC Duplex	48					
815010102	Patch Panel for 24 SC Simplex	24	3.00	540x270x52	1	550x280x300	3
815010103	Patch Panel for 24 ST	24					

TECHNICAL DRAWING (mm)

